



PA9 shown with optional air fitting

PA9 SERIES

AIR OVER HYDRAULIC PUMPS - PA9 SERIES

Part Number	Pressure Rating (psi)	Usable Oil (in ³)	Flow Rate in ³ /min		Reservoir Construction	Use with Cylinder	Weight (lbs.)
			No Load	At Load			
PA9-37	10,000	37	132	16	aluminum alloy	S/A	12

AIR OVER HYDRAULIC PUMPS - PA6 SERIES

Part Number	Pressure Rating (psi)	Usable Oil (in ³)	Flow Rate in ³ /min		Reservoir Construction	Use with Cylinder	Weight (lbs.)
			No Load	At Load			
PA6-98B	3,500	98	82	48	cast aluminum	S/A	16
PA6-98C	10,000	98		13	cast aluminum		16
PA6-122		122		13	aluminum alloy		20
PA6-98R		98					23
PA6-231		231					32
PA6-122D		122				D/A	22
PA6-231D		231					32
PA6-460D		460					44

DESCRIPTION

- Air Hydraulic Turbo speed operation offering high flow at high pressure.
- Air pressure range 40-170 PSI.
- PA9 with mounting plate to be securely fastened.
- PA9 pumps can work in horizontal or vertical position.
- PA9 Hydraulic port swivels for easy connection
- Pressure relief valve for overload protection.



PA6-98C



PA6-98R



PA6 SERIES